

Cable sleeves and spiral wraps

Braided sleeving

Characteristics

- Standard colour – black or grey
- Non-flame retardant Polyester rated at UL 94 V-2
- Available in nominal diameters from 3 to 50 mm to cover bundle diameters of 1 to 66 mm, giving flexibility when adding to or removing cables from wire looms
- For use in temperature ranges from -50°C to +150°C
- Good chemical resistance
- Halogen free
- For protecting and bundling cables and wires inside cabinets and enclosures



To stop the ends of the sleeving fraying it is necessary to heat seal the ends using a “hotwire” device. (Product Ref. WT-HSG)

Technical Information

Material	Polyester
Temperature range	-50°C to +150°C
Colour	Black or grey
Flammability rating	UL 94 V-2

1:2



Product Ref. Black	Product Ref. Grey	Nominal as supplied [mm]	Expandable diameter range [mm]	Length per mini-reel [m]
CPS3B-100	CPS3G-100	3	1 - 5	100
CPS4B-100	CPS4G-100	4	2 - 7	100
CPS5B-100	CPS5G-100	5	3 - 9	100
CPS6B-100	CPS6G-100	6	4 - 11	100
CPS8B-100	CPS8G-100	8	5 - 12	100
CPS10B-100	CPS10G-100	10	7 - 15	100
CPS12B-50	CPS12G-50	12	8 - 17	50
CPS15B-50	CPS15G-50	15	10 - 20	50
CPS20B-25	CPS20G-25	20	14 - 26	25
CPS25B-25	CPS25G-25	25	18 - 34	25
CPS30B-25	CPS30G-25	30	20 - 40	25
CPS40B-25	CPS40G-25	40	30 - 50	25
CPS50B-25	CPS50G-25	50	40 - 66	25