

ArkSwitch Übersicht / Overview



	TX FE 4	TX FE 6	TX FE 8	T1 4+1	TX 8+2	TX 4+1	TX 4+1 PoE	TX FG
Artikelnummer / Article number	3050022	3050023	3050024	3050027	3050030	3050018	3050019	3050017
Schnittstelle D-kodiert / Interface D-coded	4x 10/100 Mbit/s	6x 10/100 Mbit/s	8x 10/100 Mbit/s	4x 100 Mbit/s Full Duplex	8x 10/100 Mbit/s	4x 10/100 Mbit/s	4x 10/100 Mbit/s	—
Schnittstelle X-kodiert / Interface X-coded	—			1x 10/100/1000 Mbit/s,	1x 10/100/1000 Mbit/s, 1x 10/100/1000/2500 Mbit/s	1x 10/100/1000 Mbit/s	1x 10/100/1000 Mbit/s	5x 10/100/1000
Spannungsversorgung M12A-kodiert / Power supply M12A-coded	9-36V			9-60V	9-32V DC		14,4-33,3V DC	9-36V
Verpolungssicher / Reverse polarity protected	✓							
Betriebstemperaturbereich / Operating temperature	-40°C bis/to +70°C							
Lagertemperaturbereich / Storage temperature	-40°C bis/to +85°C							
Schutzklasse / Protection classes	IP65, IP67							
Gehäuse / Housing	Aluminium vernickelt, Edelstahl / Aluminum nickel plated, stainless steel							
Montageart / Mounting type	M6 Bohrung für Wandmontage / M6 hole for wall mounting							
EMV / EMC	DIN EN 50121-3-2; DIN EN 61000-6-2; DIN EN 55024; DIN EN 50121-3-2; DIN EN 61000-6-4; DIN EN 55032							
mechanische Belastbarkeit / Mechanical load capacity	DIN EN 61373							
Brandschutz / Fire protection	DIN EN 45545							
Konformitätserklärung und Zertifizierungen / Approvals and certifications	CE; DIN EN 50155; DIN EN 60950-1							
Maße (mm) / Dimensions (mm)	55 x 93 x 29,6	55 x 117 x 29,8	55 x 141 x 29,6	65 x 135 x 29,8	65 x 180 x 29,8	55 x 117 x 26,8	65 x 135 x 29,8	65 x 135 x 29,8
Gewicht / Weight	200g	250g	295g	400g	(tbd)	250g	370g	320g